



### **HIGH-SPEED PROCESSING**

Processing speed is approximately 2x faster than the UBA-RC series

#### SECURE CASH HANDLING

 Lockable and removable recycling module with non-volatile memory, allowing note refills in the back office for secure cash handling

#### **MODULAR DESIGN**

 Featuring easily accessible and removable modules, allowing on-site maintenance and replacement to reduce downtime

#### JCM PATENTED ANTI-STRINGING TECHNOLOGY

 Features anti-pullback mechanism to protect against banknote stringing/ manipulation

#### FRONT ACCESSIBILITY

 The complete note path, along with maintenance points, makes service quick and easy UBA<sup>®</sup> Pro-RT SS800 Cash Box UBA<sup>®</sup> Pro-RQ SH400 Cash Box

# THE UBA® PRO-RT/-RQ IS THE NEWEST GENERATION OF COMPACT BANKNOTE RECYCLER FOR 2/4 DENOMINATIONS.

The UBA® Pro-RT/-RQ features significantly improved performance while remaining compatible with the successful UBA Universal Bill Acceptor and iPRO-RC<sup>™</sup> series. The speed, reliability, and the cutting-edge technology of the UBA Pro-RT/-RQ set industry standards for banknote recyclers.







## GENERAL SPECIFICATIONS

Acceptance Rate 98% or greater

#### Accepted Banknote Size

SH400 Cash Box L: 120 mm - 170 mm (4.72 - 6.69 in.) W: 62 mm - 82 mm (2.44 - 3.22 in.)

#### SS800 Cash Box

L: 120 mm - 165 mm (4.72 - 6.49 in.) W (Recycler): 62 mm - 82 mm (2.44 - 3.22 in.) W (Cash Box): 62 mm - 85 mm (2.44 - 3.44 in.)

**Barcode Ticket** 2-way or 4-way (option) acceptance

#### Dimensions (WxHxD)<sup>1</sup>

RT: 114 (W) x 397.3 (H) x 241.5 (D) mm RQ: 114 (W) x 546.8 (H) x 241.5 (D) mm

#### Weight<sup>1</sup>

RT: 8.0 kg RQ: 11.4 kg

#### Supply Voltage DC24V ± 5% / 6A

#### Processing Speed<sup>2</sup>

Accepting to RC:	~ 2.0 - 2.5 sec
Accepting to Cash Box:	~ 3.0 – 3.5 sec
Dispensing from RC:	~ 1.5 - 2.0 sec
Collecting from RC to Cash Box:	~ 2.5 – 3.0 sec

#### **Recycling Module**

- Non-volatile memory saves the number and denominations of stored banknotes
- Lockable & Removable

#### **Recycling Module Capacity**

RT: 60 notes (30 notes x 2 drums) RO: 120 notes (30 notes x 4 drums)

#### **Cash Box**

- Type: SH400 Cash Box / SS800 Cash Box
- Cash Box Capacity: SH400 Cash Box: 400 Notes (new banknotes) SS800 Cash Box: 800 Notes (new banknotes)

<sup>1</sup> With SH400 Cash Box, no bezel

<sup>2</sup> Average per note when 10 notes are processed, speed varies depending on the communication method <sup>3</sup> Planned



www.jcmglobal.com

### Interface

USB 2.0, RS232, Photo-Coupler

**Protocols** ID-003, ID-0083, ccTalk3

Mounting Down Stacking (SS) / Up Stacking (SU)





Various Plastic Bezels



Various Metal Bezels



Recycler Lock

Removable **Recvcling Modules** 











**UBA Pro-RT** UBA Pro-RT SH400 SS800 Cash Box Cash Box

**UBA Pro-RQ** SH400 Cash Box

**UBA Pro-RO** \$\$800 Cash Box

#### THE AMERICAS HEADQUARTERS **JCM American Corporation** 925 Pilot Road Las Vegas, NV 89119

Tel: 800-683-7248 (800# for USA, Canada & Mexico) Tel: 702-651-0000

USA

#### **ASIA-PACIFIC HEADQUARTERS**

Japan Cash Machine Co., Ltd. 2-23-2 Higashi Nihonbashi, Chuo-ku Tokyo 103-0004 Japan Tel: 81-3-5962-3731

**EMEA HEADQUARTERS** JCM Europe GmbH

Muendelheimer Weg 60 D-40472 Dusseldorf Germany Tel: 49-211-530645-0

JCM Global, JCM Global logo, and other marks used herein are trademarks and registered trademarks of Japan Cash Machine Co., Ltd. and JCM American Corporation. Additional marks are registered trademarks of their respective owners. JCM Global reserves the right to change product specifications without notice.

