

## **Highly Flexible Indoor Display**

- Fully articulated to form convex, concave, and cylindrical shapes
- · Superior color performance with high color fidelity and contrast ratio
- · Ultra slim and ultra light panel design



### **FULLY ARTICULATED FLEXIBILITY**

- Each panel can flex by more than 145°, convex or concave
- Designed to form unique configurations with curvatures and circular shapes

## SUPERIOR COLOR PERFORMANCE

- Excellent grayscale level and deep black levels
- Phenomenal contrast ratio
- High fidelity brilliant colors to display creative and stunning content

## **SMART DESIGN**

- Ultra slim and ultra light panel design
- Front serviceable for easy maintenance



The FLEX LITE-S™ provides incredible flexibility with each panel curving by more than 145°. A versatile canvas for creative and unique content, the FLEX LITE-S offers a stunning contrast ratio and high color fidelity for casino entrances, art installations, and more.





# **Specifications**

|                                | FLEX LITE-S 1.875      | FLEX LITE-S 2.5        |
|--------------------------------|------------------------|------------------------|
| Physical Pitch (mm)            | 1.875                  | 2.5                    |
| Pixel Configuration            | SMD1212/1010           | SMD1515                |
| Pixel Density (pixels/m²)      | 284,444                | 160,000                |
| LED Module Dimensions (mm)     | 240 x 120              | 240 x 120              |
| Dimensions                     | Customized*            | Customized*            |
| No. of Pixels Per Module       | 128 x 64/8,192         | 96 x 48/4,608          |
| No. of Pixels Per Cabinet      | Customized*            | Customized*            |
| Module Quantity                | Customized*            | Customized*            |
| Scan Mode                      | 1/43S                  | 1/32S                  |
| Power Supply                   | 5V                     | 5V                     |
| Max. Consumption (W)           | 15                     | 15W                    |
| Max. Current (on module)       | 3A                     | 3A                     |
| Temperature                    | Max 50°C / Ave 35°C    | Max 50°C / Ave 35°C    |
| Color Temp                     | ≤10,000                | ≤10,000                |
| Brightness (nits)              | 650                    | 650                    |
| Color                          | Customized*            | Customized*            |
| Material                       | Iron                   | Iron                   |
| Horizontal Viewing Angle (°)   | 160                    | 160                    |
| Vertical Viewing Angle (°)     | 140                    | 140                    |
| Flatness                       | ≤0.3mm                 | ≤0.3mm                 |
| Module Gap (mm)                | ≤0.3mm                 | ≤0.3mm                 |
| Weight                         | Customized*            | Customized*            |
| Consumption/m <sup>2</sup> (W) | 600                    | 600                    |
| Frame Rate (Hz)                | ≥60                    | ≥60                    |
| Refresh Rate (Hz)              | 3,840                  | 3,840                  |
| IP Rating                      | IP30                   | IP30                   |
| Grey Scale                     | 12-16 bit/16,384 Level | 12-16 bit/16,384 Level |







<sup>\*</sup>The specification will be different based on configuration. Other physical pixel pitches available.

| TYPICAL APPLICATIONS |                     |                               |  |
|----------------------|---------------------|-------------------------------|--|
| Casino               | Hotel Lobby         | Window Display                |  |
| Retail Shopping      | Architecture Design | Bar & Nightclubs              |  |
| Fashion Event        | Arena               | Convention & Exhibit<br>Space |  |
| Theater Stage Design | Reception Hall      | Theme Resort                  |  |



### THE AMERICAS HEADQUARTERS

JCM American Corporation

925 Pilot Road Las Vegas, NV 89119 USA

**Tel:** 800-683-7248 (800# for USA, Canada & Mexico)

**Tel:** 702-651-0000

### **ASIA-PACIFIC HEADQUARTERS**

Japan Cash Machine Co., Ltd. 2-23-2 Higashi Nihonbashi, Chuo-ku Tokyo 103-0004 Japan

Tel: 81-3-5962-3731

### **EMEA HEADQUARTERS**

JCM Europe GmbH

Muendelheimer Weg 60 D-40472 Dusseldorf Germany

Tel: 49-211-530645-0